CATALYST

PRO-BW® PLUS

PRODUCT DETAILS

Proteus Pro-BW® Plus Catalyst Product name

Product type Catalyst for Proteus Pro-BW® Plus system

PRODUCT DESCRIPTION

Proteus Pro-BW® Plus Catalyst is a powder catalyst that is added to products within the Proteus Pro-BW® Plus system to activate the curing process to create a waterproof membrane.

APPLICATION

Proteus Pro-BW[®] Plus is appropriate for the following substrates:

Concrete

Bituminous felt • Single ply membranes •

Plywood Asphalt

Proteus Pro-BW[®] Plus is suitable for use on the following areas:

- Walkways and balconies
- Protected built-up roof
- Inverted built-up roof

- Warm built-up roof
- Warm deck
- Cold deck

Note: Some surfaces may require priming or sacrificial layers.

A wet electronic leak test is required for all inverted/buried systems prior to the waterproofing membrane being covered.

INSTALLATION

Please see the Proteus Pro-BW® Plus Application Guide for installation instructions.

CERTIFICATION

| Туре | Name | Reference |
|------|----------------------------------|-----------|
| BBA | Proteus Pro-BW [®] Plus | 18/5574 |
| EPD | Proteus Pro-BW [®] Plus | S-P-07416 |

TECHNICAL INFORMATION

| Characteristic | Value |
|-----------------------------|-------|
| Relative density (water = 1 | 1.23 |
| Physical state | solid |

| Proteus Waterproofing Limited | Telephone | 01268 777 871 | : | You | -1 |
|---------------------------------------|-----------|-----------------------------------|-----|-------------|----|
| 21a Sirdar Road | E-mail | office@proteuswaterproofing.co.uk | IN | You Tube | U |
| Brook Road Industrial Estate Rayleigh | Website | www.proteuswaterproofing.co.uk | | | БÛ |
| Essex SS6 7XF | | | (O) | | G |







CATALYST

PRODUCT DATASHEET

SIZE, FINISH AND COLOUR

| Product Code | Diameter (cm) | Height (cm) | Size ^(kg) | Colour |
|--------------|------------------|----------------|-------------------------|--------|
| BWPC01 | 20 | 14 | 1 kg | White |

SHELF LIFE AND HANDLING

- Shelf life is 12 months after point of manufacture. Check container for use by date
- Store in a cool, well-ventilated area
- Should be stored in original securely sealed containers off the ground in a covered dry store, and out of direct sunlight and away from naked flames or ignition sources
- Protect from frost

MATERIAL

Dipropylene glycol dibenzoate.

PACKAGING

Supplied in plastic containers.

LIMITATIONS OF USE

• For professional use only

CHEMICAL PROPERTIES, SAFETY GUIDANCE AND DISPOSAL

Please contact Proteus Waterproofing for details.

GUARANTEES

Defects arising from lack of maintenance or abnormal use may fall outside of the cover of the Proteus Waterproofing guarantee.

GUIDELINES AND STANDARDS

It is the responsibility of the Contractor to thoroughly familiarise themselves with all relevant Codes of Practice and Building Regulations to the works or referred in the specification.

Proteus Waterproofing take no responsibility for misinterpretation or lack of knowledge for third parties.

The works shall be carried out in accordance with the requirements of:

- **BS 6229** Flat roofs with continuously supported flexible waterproof coverings Code of practice
- **BS 8217** Reinforced bitumen membranes for roofing Code of practice
- BS 8000-0 Workmanship on construction sites Introduction and general principles
- BS 8000-4 Workmanship on building sites Code of practice for waterproofing
- LRWA Design Guide for Specifiers
- S2T Safe to Torch
- **GRO** Code of Best Practice

Proteus Waterproofing Limited 21 a Sirdar Road Brook Road Industrial Estate Rayleigh Essex SS6 7XF
 Telephone
 01268 777 871

E-mail office@proteuswaterproofing.co.uk Website www.proteuswaterproofing.co.uk





v1.0 JULY 2024