# PROTEUS PRO-TOOL SURFACE CLEANER



Product Datasheet V1.0 | September 2024



### PRODUCT DETAILS

Product name Proteus Pro-Tool Surface Cleaner

Product type Tool and surface cleaner

### PRODUCT DESCRIPTION

**Proteus Pro-Tool Surface Cleaner** is a hydrocarbon based solvent cleaning solution for tools and equipment to remove wet adhesive, primer or polyurethane liquid applied waterproofing coatings from tools and equipment, along with grease, oil, and dust from a variety of substrates such as glass, plastics, metals and more.

### **APPLICATION**

**Proteus Pro-Tool Surface Cleaner** is designed to aid in the cleaning of the following wet and cured polyurethane liquid applied waterproofing membranes:

- Proteus Cold Melt<sup>®</sup>
- Proteus Pro-BW<sup>®</sup> Plus
- Proteus Pro-BW<sup>®</sup> LO

- Proteus Pro-BW<sup>®</sup> Light
- Proteus Pro-Cold®

### INSTALLATION

- Dispense **Proteus Pro-Tool Surface Cleaner** onto a clean cloth, do not dip the towel into the cleaner as it will lead to contamination of the cleaning solution
- Wipe the surface of the contaminated substrate or tool to be cleaned. Use a fresh cloth regularly to retain the cleansing power of the solution
- Before the solvent evaporates from the surface, wipe with a clean, dry cloth
- Repeat the last two steps until no contaminants are apparent on the cloth
- The ideal installation and surface temperature is between 15°C and 25°C
- Tightly reseal container immediately after each use

#### TECHNICAL INFORMATION

Characteristic	Value	Unit
Solvent content	100	%
Viscosity at 20°C	10 - 15	cps
Application temperature	5 – 30	°C

# SIZE, FINISH AND COLOUR

Product Code	Width (cm)	Height (cm)	Volume (L)	Colour
ACCLTS05D	12	26	5	Unpigmented

Protess Waterproofing Limited
21a Sirdar Road

Prock Pound Industrial Estate Pauloi

Brook Road Industrial Estate Rayleigh
Essex SS6 7XF

Telephone E-mail Website

01268 777 871 office@proteuswaterproofing.co.uk www.proteuswaterproofing.co.uk









# PROTEUS PRO-TOOL SURFACE CLEANER



Product Datasheet imes 1.0 | September 2024

## SHELF LIFE AND HANDLING

- Shelf life is 24 months after point of manufacture. Check container for use by date
- Store in an upright position in a dry and secure location, not in direct sunlight
- Storage in low or high temperatures are to be avoided. Ideal storage temperatures are 5° 30°C

### MATERIAL

Hydrocarbon based solvent.

## **PACKAGING**

Packaged in sealed plastic containers.

### LIMITATIONS OF USE

For professional use only.

### GUARANTEES

Defects arising from lack of maintenance or abnormal use may fall outside of the cover of the Proteus Waterproofing guarantee.

### GUIDELINES AND STANDARDS

It is the responsibility of the Contractor to thoroughly familiarise themselves with all relevant Codes of Practice and Building Regulations to the works or referred in the specification.

Proteus Waterproofing take no responsibility for misinterpretation or lack of knowledge for third parties.

The works shall be carried out in accordance with the requirements of:

BS 6229
 Flat roofs with continuously supported flexible waterproof coverings - Code of practice

BS 8217 Reinforced bitumen membranes for roofing - Code of practice

BS 8000-0 Workmanship on construction sites - Introduction and general principles
 BS 8000-4 Workmanship on building sites - Code of practice for waterproofing

LRWA Design Guide for Specifiers

• S2T Safe to Torch

GRO Code of Best Practice





