

SAFETY DATA SHEET

Pro-Prime® SA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Pro-Prime® SA

Product no.

ACPRSA05NV1.0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Primer Self-Adhesive

Use descriptors (UK REACH)

Sectors of use	Description
SU 19	Building and construction work

Product category	Description
PC9a	Coatings and Paints, Fillers, Putties, Thinners

Process category	Description
PROC10	Roller application or brushing

Uses advised against

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)

Process category	Description
PROC7	Industrial spraying
PROC11	Non industrial spraying
PROC19	Hand-mixing with intimate contact and only PPE available

1.3. Details of the supplier of the safety data sheet

Company and address

Proteus Waterproofing Ltd

21a Sirdar Road, Brook Road Industrial Estate

SS6 7XF Rayleigh, Essex

England

+44 (0) 1268 777871 Office Mon-Fri 08:30-17:00 outside of these hours call emergency numbers

www.proteuswaterproofing.co.uk

E-mail

enquiries@proteuswaterproofing.co.uk

Revision

16/11/2022

SDS Version

1.0

1.4. Emergency telephone number

In emergency call +44 (0) 1865 407 333

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.
Aquatic Acute 1; H400, Very toxic to aquatic life.
Aquatic Chronic 1; H410, Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)
Very toxic to aquatic life with long lasting effects. (H410)

Safety statement(s)

General

-

Prevention

Do not handle until all safety precautions have been read and understood. (P202)
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Keep container tightly closed. (P233)
Keep only in original packaging. (P234)
Ground and bond container and receiving equipment. (P240)
Use explosion-proof [electrical/lighting/ventilating] equipment. (P241)
Use non-sparking tools. (P242)
Take action to prevent static discharges. (P243)
Avoid breathing mist/vapour. (P261)
Wash hands thoroughly after handling. (P264)
Do not eat, drink or smoke when using this product. (P270)
Use only outdoors or in a well-ventilated area. (P271)
Avoid release to the environment. (P273)
Wear face protection/protective gloves/protective clothing. (P280)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
IF ON SKIN: Wash with plenty of water and soap. (P302+P352)
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. (P303+P361+P353)
IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Call a POISON CENTER/doctor if you feel unwell. (P312)
Do NOT induce vomiting. (P331)
If skin irritation occurs: Get medical advice/attention. (P332+P313)
If eye irritation persists: Get medical advice/attention. (P337+P313)
Take off contaminated clothing and wash it before reuse. (P362+P364)
In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)
Collect spillage. (P391)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)
Store locked up. (P405)

Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

heptane
methyl ethyl ketone
acetone

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.
EUH401, To avoid risks to human health and the environment, comply with the instructions for use.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
heptane	CAS No.: 142-82-5 EC No.: 205-563-8 UK-REACH: Index No.: 601-008-00-2	25-40%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
methyl ethyl ketone	CAS No.: 78-93-3 EC No.: 201-159-0 UK-REACH: Index No.: 606-002-00-3	25-40%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
acetone	CAS No.: 67-64-1 EC No.: 200-662-2 UK-REACH: Index No.: 606-001-00-8	25-40%	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Keep only in original packaging.

Storage temperature

DO NOT store in pits basements or areas where vapours may be trapped

DO NOT cut, drill, grind, weld or perform similar operations on or near containers

Container's, even those that have been emptied, may contain explosive vapours.

Keep container earthed, risk of static build up that could cause fire or explosion.

Store in a lockable flammable liquid storage area

Store away from incompatibles
 Ensure good ventilation and/or extraction at the workplace
 Always release caps or seals slowly to ensure slow dissipation of vapours
 Avoid static electricity, consider antistatic clothing, footwear and ppe.
 Do not breathe vapours or spray mist.
 Keep away from food for human consumption and animal feeds.

Incompatible materials

Amines
 Avoid static electricity, consider antistatic clothing, footwear and ppe.
 Bases
 isocyanate
 Organic solvents
 Oxidising Agents
 Reducing agents
 Strong acids
 Strong alkalines

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

heptane
 Long term exposure limit (8 hours) (ppm): 500
 Long term exposure limit (8 hours) (mg/m³): 2085

methyl ethyl ketone
 Long term exposure limit (8 hours) (ppm): 200
 Long term exposure limit (8 hours) (mg/m³): 600
 Short term exposure limit (15 minutes) (ppm): 300
 Short term exposure limit (15 minutes) (mg/m³): 899

Annotations:
 BMVG = Biological Monitoring Guidance Value exists
 Sk = Can be absorbed through the skin and lead to systemic toxicity.

acetone
 Long term exposure limit (8 hours) (ppm): 500
 Long term exposure limit (8 hours) (mg/m³): 1210
 Short term exposure limit (15 minutes) (ppm): 1500
 Short term exposure limit (15 minutes) (mg/m³): 3620

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

acetone

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - Workers	Inhalation	1210 mg/m ³
Short term – Local effects - Workers	Inhalation	2420 mg/m ³

heptane

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	300 mg/kg bw/day
Long term – Systemic effects - Workers	Inhalation	2085 mg/m ³

methyl ethyl ketone

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	1161 mg/kg bw/day
Long term – Systemic effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - Workers	Inhalation	900 mg/m ³

PNEC

acetone

Route of exposure	Duration of Exposure	PNEC
Freshwater		10.6 mg/L
Freshwater sediment		30.4 mg/kg
Intermittent release (freshwater)		21 mg/L
Marine water		1.06 mg/L
Marine water sediment		3.04 mg/kg
Sewage treatment plant		100 mg/L
Soil		29.5 mg/kg

methyl ethyl ketone

Route of exposure	Duration of Exposure	PNEC
Freshwater		55.8 mg/L
Freshwater sediment		284.74 mg/kg
Intermittent release (freshwater)		55.8 mg/L
Marine water		55.8 mg/L
Marine water sediment		284.7 mg/kg
Predators		1 g/kg
Sewage treatment plant		709 mg/L
Soil		22.5 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Contaminated leather items such as shoes, boots, belts and watch bands should be removed and destroyed.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

8.3. Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
Ensure adequate ventilation, use suitable respiratory protection in enclosed or poorly ventilated areas.	Suitable respiratory protection advice for the correct personal selection can be obtained from EN529:2005			

Skin protection

Work situation	Recommended	Type/Category	Standards
Do not allow clothing wet with material to stay in contact with skin.	Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-



Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Work situation	Recommended	Type/Category	Standards
Discard items which cannot be decontaminated, including leather shoes, boots, belts, watch straps, gloves etc.	Contaminated garments should be removed promptly and should not be reused until they have been decontaminated, do NOT allow garments to be decontaminated/cleaned in household laundry		
Contaminated workwear MUST NOT leave site or be washed in household laundry	Store protective clothing separately from other clothing, DO NOT wash in normal laundry		



Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
In the event of short termed exposure or low concentrations	Consider the following when selecting work gloves, material, compatibility, degradation, failure time, permeability. The gloves resistance to chemicals should be checked prior to use, wear time depends on duration and type of use.			
Discard items which cannot be decontaminated, including leather shoes, boots, belts, watch straps, gloves etc.	Protect hands with Cat III work gloves (see standard EN374, UKCA marked to show it conforms to applicable standards)			



Eye protection

Type	Standards
Face shield	EN166
Safety Goggles	EN166:2001



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Green

Odour / Odour threshold

No data available

pH

No data available

Density (g/cm³)

Testing not relevant or not possible due to the nature of the product.

Relative density

0.9

Kinematic viscosity

No data available

Particle characteristics

No data available

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

No data available

Vapour pressure

No data available

Relative vapour density

No data available

Decomposition temperature (°C)

Not applicable

Data on fire and explosion hazards

Flash point (°C)

-5

Ignition (°C)

No data available

Auto flammability (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

No data available

n-octanol/water coefficient

No data available

Solubility in fat (g/L)

No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No data available

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Amines

Avoid static electricity, consider antistatic clothing, footwear and ppe.

Bases

isocyanate

Organic solvents

Oxidising Agents

Reducing agents

Strong acids

Strong alkalines

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Accidental ingestion of the material may be damaging to the health of the individual.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of vapours or aerosols (mists/fumes), generated by the material during the course of normal handling, may be damaging to health of the individual.

Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction times, slurred speech and may progress to unconsciousness.

Serious poisonings may result in respiratory depression and may be fatal.

Asthma like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with a sudden onset of persistent asthma like symptoms within minutes or hours of a documented exposure to the irritant.

Skin sensitisation

Entry into the blood-stream through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Open cuts, abraded or irritated skin should not be exposed to this material.

The material may accentuate any pre-existing dermatitis condition.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

It is assumed it contains a substance which can cause developmental effects and an increase in birth defects.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term exposure to respiratory irritants may result in airways disease, involving difficulty in breathing and related whole-body problems.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

None known.

Other information

There is a danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed, the material can cause serious damage to workers if exposed to it for long periods.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

None known.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

DO NOT allow wash water from cleaning or process equipment to enter drains.

EWC code

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	UN1133	ADHESIVES	Class: 3 Labels: 3 Classification code: F1  	II	Yes	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1133	ADHESIVES	Class: 3 Labels: 3 Classification code: F1  	II	Yes	Limited quantities: 5 L EmS: F-E S-D See below for additional information.
IATA	UN1133	ADHESIVES	Class: 3 Labels: 3 Classification code: F1	II	Yes	See below for additional information.

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
					

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●3YE

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

E1 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 100 tonnes / (upper-tier): 200 tonnes

Additional information

Not applicable.

Sources

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

SU 19 = Building and construction work

PROC10 = Roller application or brushing

PC9a = Coatings and Paints, Fillers, Putties, Thinners

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Steven D'Silva Quality Manager

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en